

2D WIRELESS HD ULTRA RUGGED

DCCode®


DC 9122HD



ULTRA-RUGGED—INDUSTRY'S TOUGHEST DESIGN.



100 METERS OPEN TRANSMISSION DISTANCE.



32 BITS CPU – SUPER DECODING ABILITY.



2200MAH LARGE-CAPACITY LITHIUM BATTERY

HD

TECHNICAL SPECIFICATIONS

Scan Type	617nm LED Aimer, White LED
Lighting Aimer	CMOS 1080*1280 pixels
Scan Width	5cm to 50cm
Field of View	Horizontal 44°,vertical34°
Scan Angle	Rotation 360° / Yaw ±70° / Pitch ±55°
Resolution	3 mil
CPU	ARM 32 bit Cortex
Contrast	20%
Error Rate	≤1/5 million
Interface	Receiver: USB-HID, USB-COM; Bluetooth : HID, BLE
Wireless Comm	Pairing dedicated receiver: 2.4Gcommunication Pairing mobile Bluetooth devices: Dual-mode Bluetooth
Prompt Mode	Buzzer, LED
Transmission distance	100 meters (Open Distance)
Decoding Capability	UPC-A, UPC-E,Code128, EAN-13, EAN-8, ISBN, Code 93, UCC/EAN-128,GS1Code39,Code 39FullASCII,Codabar,Interleaved 2 of 5,Databar,MSI,Code11, ISBN,ISSN,China post,etc
Electric Voltage	5V DC
Operating Current	260mA
Light Immunity	0-100,000 Lux
IP Rating	IP66
Mechanical Parameters	
Dimensions	172mm x 93mm x 68mm
Weight	169g
Environmental Parameters	
Working Temperature	-20°C ~ 50°C
Storage Temperature	-40°C ~ 70°C
Humidity	5% to 95% Relative Humidity, Non Condensing
Drop Test	3m
Warranty	
24 Months against any manufacturing defect	


APPLICATIONS



AEROSPACE



AUTOMOTIVE



ELECTRONICS



RAILWAY



WAREHOUSE



DCCode®

hello@dcodeinternational.in



www.dcodeinternational.in

DELHI NCR MUMBAI AHMEDABAD SURAT TIRUPUR CHENNAI LUDHIANA PUNE KOLKATA COIMBATORE

