

# MOBILE LABEL PRINTER

# DCcode®

# DC3M

- USB + Bluetooth
- Direct USB Charging
- 2500mAh Battery
- Prints Both Labels & Receipts
- Supports TSPL, EPL, ZPL, DPL, CPCL, ESC/POS Commands



# 3 Inch

## Technical Specifications

Resolution	203 DPI
Print method	Direct Thermal
Print speed	70 mm (2.7") / s
Print width	72mm (2.8")
Max.print length	1778mm (70")
<b>Media</b>	
Media type	Continuous, gap, black mark
Media width	25.4 mm - 76 mm
Media thickness	0.06 mm - 0.16 mm
<b>Performance Features</b>	
Processor	32-bit CPU
Memory	8MB Flash Memory / 8MB SDRAM
Interface	USB + Bluetooth
Screen	OLED (0.96") Resolution:128x64pix
Sensors	1.Gap Sensor 2.Cover Opening Sensor 3.Black mark sensor
1D Barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN, etc.
2D Barcode	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Internal Fonts	8 alpha-numeric bitmap fonts, Windows fonts can be downloaded
Rotation	0°, 90°, 180°, 270°
Emulation	TSPL ZPL, EPL, DPL, CPCL, ESC/POS
Dimension	120x112x60mm
Weight	400g
Print Head Life	30KM
Operating System	Windows / iOS / Android
SDK	Windows / iOS / Android
USB	DC 5V/2A
Battery	2500mAh
Storage Temp	-40° ~ 60°C(-40~140°F) Humidity: 10 ~ 90% non-condensing
Operational Temp	5° ~ 40°C(41~104°F) Humidity: 25 ~ 85% non-condensing



# DCcode®

hello@dcodeinternational.in



www.dcodeinternational.in



DELHI NCR MUMBAI AHMEDABAD SURAT TIRUPUR CHENNAI LUDHIANA PUNE KOLKATA COIMBATORE

Technical Support: +91 9999571649