

THERMAL RECEIPT PRINTER

DCcode[®]

DC3R1

- USB + LAN Standard
- Print speed up to 230mm/s
- Print Width 72mm
- Auto Cutter
- Optional: Bluetooth, Wi-Fi



Technical Specifications

Printing Method	Direct Thermal
Paper Width	79.5 ± 0.5mm
Print Width	72mm
Column Capacity	576 dots / line
Printing Speed	230 mm/s
Interface	USB + LAN
Line Spacing	3.75mm (Adjustable by Command)
Column number	80mm paper: Font A - 48 columns/ Font B- 64 columns
Character Size	ANK, FontA: 1.5x3.0mm FontB: 1.1x2.1mm
Auto Cutter	Available
Barcode Character	
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR /CODE93/CODE128
2D Barcode	QR CODE / PDF 417
Input Buffer	96 Kbytes
NV Flash	256Kbytes
Power	
Power Adaptor	AC 100 ~ 240V, 50 ~ 60Hz
Printer Input	DC 24V/2.5A
Cash Drawer	DC 24V/1A
Physical Characteristics	
Weight	1.01 KG
Dimensions	192*145.2*146.3mm
Environmental	
Work	0° ~ 45°C (Humidity 10 ~ 80%)
Storage	-10° ~ 60° (Humidity 10 ~ 90%)
Software	
Emulation	ESC/POS
Driver	Windows/JPOS/Linux/OPOS/Android/Mac
Utility	Windows & Linux Test Utility
SDK	iOS, Android, Windows



DCcode[®]

hello@dcodeinternational.in



www.dcodeinternational.in



DELHI NCR MUMBAI AHMEDABAD SURAT TIRUPUR CHENNAI LUDHIANA PUNE KOLKATA COIMBATORE

Technical Support: +91 9999571649