

# THERMAL RECEIPT PRINTER

**DCCode**<sup>®</sup>

# DC3R3



- USB + LAN + RS232
- Print speed up to 260mm/s
- Print Width 72mm
- Auto Cutter
- Optional: Bluetooth, Wi-Fi



## Technical Specifications

<b>Printing Method</b>	Direct Thermal
<b>Paper Width</b>	79.5 ± 0.5mm
<b>Print Width</b>	72mm
<b>Column Capacity</b>	576 dots / line
<b>Printing Speed</b>	260 mm/s
<b>Interface</b>	USB + LAN + RS232
<b>Line Spacing</b>	3.75mm (Adjustable by Command)
<b>Column number</b>	80mm paper: Font A - 48 columns/ Font B- 64 columns
<b>Character Size</b>	ANK, FontA: 1.5x3.0mm   FontB: 1.1x2.1mm
<b>Auto Cutter</b>	Available
<b>Barcode Character</b>	
<b>1D Barcode</b>	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR /CODE93/CODE128
<b>2D Barcode</b>	QR CODE / PDF 417
<b>Input Buffer</b>	96 Kbytes
<b>NV Flash</b>	256Kbytes
<b>Power</b>	
<b>Power Adaptor</b>	AC 100 ~ 240V, 50 ~ 60Hz
<b>Printer Input</b>	DC 24V/2.5A
<b>Cash Drawer</b>	DC 24V/1A
<b>Physical Characteristics</b>	
<b>Weight</b>	1.01 KG
<b>Dimensions</b>	192*145.2*146.3mm
<b>Environmental</b>	
<b>Work</b>	0° ~ 45°C (Humidity 10 ~ 80%)
<b>Storage</b>	-10° ~ 60° (Humidity 10 ~ 90%)
<b>Software</b>	
<b>Emulation</b>	ESC/POS
<b>Driver</b>	Windows/JPOS/Linux/OPOS/Android/Mac
<b>Utility</b>	Windows & Linux Test Utility
<b>SDK</b>	iOS, Android, Windows



**DCCode**<sup>®</sup>

hello@dcodeinternational.in

www.dcodeinternational.in



DELHI NCR MUMBAI AHMEDABAD SURAT TIRUPUR CHENNAI LUDHIANA PUNE KOLKATA COIMBATORE

Technical Support: +91 9999571649