

DIRECT THERMAL LABEL PRINTER

DCcode®

DC421 D

- USB + LAN Standard
- Fast print speed 152mm/s or 6 IPS
- Supporting TSPL, EPL, ZPL, DPL Commands
- Optional: Bluetooth, Wi-Fi, Cutter, Peeler



Bluetooth

Wi Fi

203 DPI



Technical Specifications

Resolution	203 DPI
Print method	Direct Thermal
Print speed	152 mm (6") / s
Max.print width	108mm (4.09")
Max.print length	1778mm (70")
Media	
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	25.4-115mm (1.0"-4.6")
Media thickness	0.06~0.254 mm (2.36~10mil)
Media core diameter	25.4 ~ 76.2 mm (1" ~ 3")
Label length	10 ~ 1778 mm (0.39" ~ 70")
Performance Features	
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory upto Max.4GB
Interface	USB + LAN
Processor	32 Bit CPU
1D Barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN, etc. PDF-417, Maxicode, DataMatrix, QR code, Aztec
2D Barcode	8 alpha-numeric bitmap fonts, Windows fonts can be downloaded
Internal Fonts	1.Gap sensor 2.Cover Opening sensor 3.Black mark sensor
Sensors	TSPL ZPL, EPL, DPL
Emulation	215 mm (D) x 178 mm (W) x 155 mm (H)
Dimension	1.31 kg
Weight	25KM
Print Head Life	Windows / Linux / Mac
Driver	Windows / iOS / Android
SDK	AC 110-240V,1.8A, 50-60Hz
Input	DC 24V, 2.5A, 60W
Output	Cutter, Peel Off, Bluetooth, Wi-Fi, External Stand
Optionals	
Operational Temp	5° ~ 40°C(41~104°F)Humidity: 25 ~ 85% non-condensing



DCcode®



hello@dcodeinternational.com



www.dcodeinternational.com

DELHI NCR MUMBAI AHMEDABAD SURAT TIRUPUR BENGALURU LUDHIANA PUNE DEHRADUN COIMBATORE

Technical Support: +91 9999571649

