

THERMAL TRANSFER LABEL PRINTER

DCCode®

DC421 Pro

- USB + LAN
- Print speed up to 127mm/s or 5 IPS
- Ribbon roll capacity 300m, 25.4mm Ribbon Roller (Outer roll ribbon)
- Supporting TSPL, EPL, ZPL, DPL Commands
- Optional: Bluetooth, Wi-Fi



Bluetooth



Wi-Fi



203 DPI

Technical Specifications

Resolution	203 DPI
Print method	Thermal Transfer / Direct Thermal
Print speed	127 mm (5") / s
Max.print width	104mm (4.09")
Max.print length	1778mm (70')
Media	
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	25.4-118mm (1.0"-4.6")
Media thickness	0.06~0.254 mm (2.36~10mil)
Media core diameter	25.4 ~ 76.2 mm (1" ~ 3")
Label length	10 ~ 889 mm(0.39" ~ 35")
Label roll capacity	127 mm (5") OD (External Diameter)
Ribbon capacity	Max.300m
Ribbon width	110 mm
Ribbon core	25.4 mm (1")
Performance Features	
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory upto Max.4GB
Interface	USB + LAN
1D Barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN, etc. PDF-417, Maxicode, DataMatrix, QR code, Aztec
2D Barcode	
Internal Fonts	8 alpha-numeric bitmap fonts, Windows fonts can be downloaded
Sensors	1.Gap sensor 2.Cover sensor 3.Black mark sensor 4.Ribbon sensor
Emulation	TSPL ZPL, EPL, DPL
Dimension	299 mm (D) x 235 mm (W) x 198.3 mm (H)
Weight	2.55 kg
Print Head Life	25KM
Driver	Windows / Linux / Mac
SDK	Windows / iOS / Android
Input	AC 110-240V,1.8A, 50-60Hz
Output	DC 24V, 2.5A, 60W
Optionals	Cutter, Peel Off, Bluetooth, Wi-Fi, External Stand
Operational Temp	5° ~ 40°C(41~104°F)Humidity: 25 ~ 85% non-condensing



DCCode®

hello@dcodeinternational.com

www.dcodeinternational.com



Technical Support: +91 9999571649