

# THERMAL RECEIPT PRINTER

# DCode®

# DCRP20

- USB + Bluetooth
- Speed 90mm/s
- 2 Inch Width
- Receipts Only Printer
- Supports ESC/POS Commands



## 2 Inch

## Technical Specifications

Resolution	203 DPI
Printing method	Direct thermal
Paper width	57.5±0.5mm
Print width	48 mm
Column capacity	384 dots/line
Printing speed	90 mm/s
Interface	USB / USB+Bluetooth
Line spacing	3.75mm (Adjustable by commands)

### Performance Features

Interfaces	USB+Bluetooth(1 or 1), Optional: USB+Serial+Bluetooth(1 or 1)
Memory	64 Kbytes
NV Flash	1 M
Emulation	ESC/POS

### Fonts Symbology

Character size	Afont A: 12*24, Font B: 9*17, CHN: 24*24
Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128/QRCODE/PDF417
Extension character sheet	PC347(Standard Europe) / Katakana / PC850( Multilingual) / PC860(Portuguese) / PC863(Canadian-French)/PC865(Nordic)/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866(Cyrillic#2)/PC852(Latin2)/PC858/IranII/Latvian/Arabic/PT151(1251)
Input buffer	96 Kbytes
NV Flash	256 bytes

### Other Characteristic

Power adaptor	AC 100V/240V, 50 ~ 60Hz, 1A
Power source	DC 9V / 2A
Cash drawer	DC 12V / 1A
Weight	0.48 kg
Dimensions	138 * 119 * 101mm(D*W*H)
Work environment	Temperature(0 ~ 45°C); humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60°C); humidity(10 ~ 90%)
Printer head life	50Km
Emulation	ESC/POS
Driver	Windows/Linux/Android/Mac



# DCode®

hello@dcodeinternational.in

www.dcodeinternational.in



DELHI NCR MUMBAI AHMEDABAD SURAT TIRUPUR CHENNAI LUDHIANA PUNE KOLKATA COIMBATORE

Technical Support: +91 9999571649